

GETCERTKEY



GETCERTKEY

100% guarantee you pass IT cert exam!

Instant Update

We are checking our exam questions all the time.



Security & Privacy



24/7 customer support

Free Demo Download

Try before you buy, Download a free sample of any of our exam questions and answers.



One Year Free Update

Free update is available within One Year after your purchase.



<http://www.getcertkey.com>

No help, Full refund!

Exam : **650-968**

Title : Configuring Cisco UCS and
Cisco Catalyst 3000 for Vblock
Series 100

Vendor : Cisco

Version : DEMO

NO.1 In the Cisco Catalyst 3000 switch, what is the maximum power sourced for PoE+ and UPoE?

- A. 60 W and 60 W
- B. 30 W and 30 W
- C. 15Wand15W
- D. 15Wand30W
- E. 30 W and 60 W

Answer: E

NO.2 What is the EEM policy that is defined within the CLI configurations?

- A. An applet
- B. tbc script
- C. tcl script
- D. txt script
- E. bat script

Answer: A

NO.3 Which enhanced feature on the Cisco Catalyst switch monitors and collects flow statistics on uplink ports?

- A. Flexible NetFlow
- B. OoS Policing
- C. QoS Shaping
- D. Ethereal

Answer: A

NO.4 What is The default username and password on the Cisco UCS C220 M3 Rack Server?

- A. admin, password
- B. admin, admin
- C. admin, Cisco
- D. Cisco. Cisco

Answer: A

NO.5 The Cisco UCS C220 M3 Rack Server is based on which Intel processor family?

- A. Intel Xeon processor E5-2600 product family
- B. Intel Xeon processor E6-2600 product family
- C. Intel Xeon processor E4-2600 product family
- D. Intel Xeon processor E7-2600 product family

Answer: A

NO.6 Which one of the following features can be configured for high availability on a Cisco Catalyst 3000 switch?

- A. QoS
- B. VRF-Lite
- C. EVN

D. VRF

E. UPoE

Answer: B

NO.7 On a Cisco Catalyst switch, what is the entity that defines an event and The actions to be taken when that event occurs?

A. Network exception

B. SNMP MIB

C. Syslog table

D. SNMP trap

E. EEM policy

Answer: E

NO.8 A customer is using a Cisco Catalyst 3000 Series switch, with the following requirements:

Multiple third-party customers will need their own routing table

Overlapping IP addresses will and could occur Which feature would you recommend?

A.BGP

B.OSPF

C.EIGRP

D.EVN

E.VRF-Lite

Answer: E