

GETCERTKEY



GETCERTKEY

100% guarantee you pass IT cert exam!

Instant Update

We are checking our exam questions all the time.



Security & Privacy



24/7 customer support

Free Demo Download

Try before you buy, Download a free sample of any of our exam questions and answers.



One Year Free Update

Free update is available within One Year after your purchase.



<http://www.getcertkey.com>

No help, Full refund!

Exam : **HAT-680**

Title : HITACHI DATA SYSTEMS
QUALIFIED PROFESSIONAL -
STORAGE ADMINISTRATION

Vendor : Hitachi

Version : DEMO

NO.1 You are installing Hitachi Device Manager and need to verify the existence of the two pre-defined user profiles. Which two are they? (Choose two.)

- A. administrator
- B. hauser
- C. root
- D. system

Answer: B,D

NO.2 When using Hitachi Device Manager to map external volumes to a VSP storage system, what are three external volume attributes that can be set? (Choose three.)

- A. cache mode
- B. CLPR
- C. emulation type
- D. SLPR
- E. internal LDEV number

Answer: A,B,E

NO.3 You are using Hitachi Storage Navigator to create a LUN on a VSP storage system. After completing the operation you observe that the LUNs you created are not listed. Which action would enable Hitachi Device Manager (HDvM) to see these LUNs?

- A. Log back into Storage Navigator and re-create the LUNs.
- B. Perform a host refresh using the ResetHost command.
- C. Execute the HDvM CLI command SetLunRecovery.
- D. Refresh the storage system.

Answer: D

NO.4 You are managing a Hitachi Device Manager environment and want to use the Element Manager to configure the Fibre Channel ports on a Hitachi VSP storage system. Which two Fibre Channel port operations are permitted? (Choose two.)

- A. Reset the port.
- B. Set the connection type.
- C. Set the port attribute.
- D. Set the port offline.

Answer: B,C

NO.5 You want to log in to Hitachi Device Manager (HDvM), but an Internal Server Error is displayed in the Web Client. You can ping the HDvM server, but no other operations can be performed. When troubleshooting, which two settings should you verify? (Choose two.)

- A. That the firewall is open for port 23015.
- B. That the HDvM's licensed capacity is sufficient.
- C. That Common Component services are running.
- D. That the memory heap size is sufficient.

Answer: C,D

NO.6 You are using the Allocate Storage wizard in Hitachi Device Manager and you want to identify the storage. Which two specification options are available? (Choose two.)

- A. volume type
- B. volume label
- C. volume free space
- D. volume location

Answer: A,D

NO.7 When configuring external storage on a VSP storage system, what happens when the Inflow Control option is set to Enable?

- A. Writes will be rejected when the external volume cannot be accessed.
- B. Writes will be rejected when the cache usage is above threshold 1.
- C. Writes will be accepted when the external volume cannot be accessed.
- D. Writes will be rejected when the cache usage is above threshold 2.

Answer: A

NO.8 In which Hitachi Device Manager screen is the Allocate Like Volumes feature available?

- A. Hosts
- B. Allocate Storage
- C. Dynamic Provisioning
- D. Allocate Volumes to Multiple Hosts

Answer: A

NO.9 You want to restore the HiRDB database on a Hitachi Command Suite (HCS) server. Which two operations should you perform? (Choose two.)

- A. Edit the server.properties file to prepare the database synchronization.
- B. Open the Utility tab in the HCS GUI and select the Restore Database function.
- C. Run the HiRDB backup/restore wizard and select the backup file to be restored.
- D. Use the hcmdsdb /restore command to initiate the restore process.

Answer: A,D

NO.10 A storage administrator needs to allocate storage to a host using Hitachi Device Manager. In the GUI, which two locations would they navigate to when allocating the storage? (Choose two.)

- A. Parity Groups view
- B. Admin Groups view
- C. Logical Groups view
- D. Mobility Groups view

Answer: A,C