

GETCERTKEY



GETCERTKEY

100% guarantee you pass IT cert exam!

Instant Update

We are checking our exam questions all the time.



Security & Privacy



24/7 customer support

Free Demo Download

Try before you buy, Download a free sample of any of our exam questions and answers.



One Year Free Update

Free update is available within One Year after your purchase.



<http://www.getcertkey.com>

No help, Full refund!

Exam : **HP0-J56**

Title : 3PAR Solutions Advanced
Service and Support

Vendors : HP

Version : DEMO

NO.1 You are configuring vStorage APIs for Array Integration (VAAI) Plugin using an HP 3PAR System. What does the UNMAP functionality provide?

- A. It provides notification that the LUN is thin provisioned and gets quota exceeded behavior check condition from the array.
- B. It offers block zeroing used in the combination with HP 3PAR Thin technologies.
- C. It avoids locking an entire LUN during VMFS metadata update.
- D. It performs a full copy of data within the array.

Answer: B

NO.2 How are the ports numbered on a V400 or V800 PCI adapter?

- A. From left to right
- B. From bottom to top
- C. From right to left
- D. From top to bottom

Answer: A

NO.3 Which method can be used to determine that a node has joined a cluster?

- A. The node status LED is green and flashing slowly
- B. The cluster name displays in green in SPOCC
- C. The node name displays in green in the Hardware Inventory tab of IMC
- D. The output of cli%showcluster contains a node state of Clustered

Answer: A

NO.4 After upgrading VMware environment to the latest version, you want to take advantage of the VAAI integration that avoids locking an entire LUN during VMFS metadata update. Which VAAI primitive provides this feature?

- A. ATS
- B. Write_Same
- C. UNMAP
- D. VM STUN

Answer: A

NO.5 Which statements are true regarding V800 controller nodes? (Select two)

- A. Each PCI card may have a maximum of two FC ports.
- B. Each controller node has nine PCI slots.
- C. Controller nodes support a maximum of 18 FC connections.
- D. A PCI slot supports dual-port Converged Network Adapters.
- E. Each controller node has four management Ethernet ports.

Answer: D,E

NO.6 Your customer has an existing 3PAR T400 array with 128 FC disks. The customer has been using

System Reporter and now requires policy driven tiering. In addition to the disks, which software is required to achieve this?

- A. Command View
- B. System Tuner
- C. Dynamic Optimization
- D. Adaptive Optimization

Answer: D

NO.7 Which statement is true when comparing F400 and V400 controller nodes?

- A. Control memory has increased from 6 GB to 16 GB.
- B. PCI slots have increased from 6 to 12 per controller node.
- C. Data memory has increased from 6 GB to 16 GB
- D. Maximum battery life has reduced from 25 to 15 minutes when fully charged.

Answer: A

NO.8 You are the installing System Reporter with Adapter Optimization. When adding the INSERTV system to be sampled, the customer informs you that they do not want to use the default HP 3PAR account CLI user, but rather they want to create a specific user for the application. What are the minimum permissions the customer-created user requires?

- A. Create
- B. Edit
- C. Browse
- D. Super

Answer: D

NO.9 What is the best way to manage 15 VMware hosts and 12 Hyper-V hosts to be able to present Virtual Volumes (VVols) quickly?

- A. Volume sets
- B. Provisioned sets
- C. Host groups
- D. Group sets

Answer: B

NO.10 Which resource should be used when installing an additional controller node to an HP 3PAR Storage System?

- A. HP 3PAR Storage System User and Administration Guide
- B. HP 3PAR Storage System Controller Node Upgrade Poster
- C. HP 3PAR Storage System Service and Maintenance Guide
- D. HP 3PAR Storage System Upgrade Guide

Answer: A